

## Mini Horns Sirens Buzzer / Signal Horn 482 Buzzer WM Contin. tone 6VDC GY



Part No.: 482.347.13



MECHANICAL DATA	
Height	80 mm
Diameter	70 mm
Materials	PC/ABS
Housing colour	Grey
Protection category	IP33
Connection	Screw terminals
cross-sectional area maximum	1,50mm <sup>2</sup> / 16AWG
Cable entry	Through hole
Cable entry maximum	d = 9 mm
Type of fixing	Wall mounting
Service life optical	300 h minimum
Acoustic service life	300 h minimum
Working temperature minimum	-20°C
Working temperature maximum	+60°C
Weight with packaging	180 g
Product weight	160 g
ELECTRICAL DATA	
Operating voltage	6V
Operating voltage type	DC
Operating voltage tolerance	+/- 10%
Rated operational voltage	6 VDC
Rated operational current	80 mA
Rated inrush current	<5A
Protection class	Protection class 1
Pollution degree	2
Request to external PSU	SELV/PELV
ACUSTICAL DATA	
Volume/dB(max) at 1m distance	83,0 dB dB(A)
Acoustic signal image	Continuous tone
Audio frequency	500 Hz



For additional installation and mounting information, refer to the appropriate user guide at [www.werma.com](http://www.werma.com). This printed copy is for information only and is subject to alteration.