

LineLIGHT Fusion 300 24V RGB Clip



Part No.: **300.100.17**



MECHANICAL DATA

| | |
|-----------------------------|------------------------------------|
| Length | 345 mm |
| Width | 33 mm |
| Height | 23 mm |
| Materials | Aluminium PC Stainless steel |
| Dome colour | Trancluent |
| Housing colour | Black |
| Protection category | IP54 IP65 |
| Connection | M12 plug 5-pole |
| Type of fixing | Built-in mounting |
| Working temperature minimum | -30°C |
| Working temperature maximum | +50°C |
| Min. Tightening torque | 0.3Nm |
| Max. Tightening torque | 0.6Nm |

OPTICAL DATA

| | |
|----------------------|------------------|
| Light source | LED |
| Light colour | MC 7 colours |
| Optical signal image | Permanent |
| Service life optical | 50,000 h maximum |

ACOUSTIC DATA

| | |
|-----------------------|-----------------|
| Acoustic service life | 5,000 h minimum |
|-----------------------|-----------------|

APPROVAL DATA

| | |
|-------------------------------|-----------------------|
| Conforms with CE | Yes |
| Conforms with RoHS directive | No |
| WEEE | Yes |
| Conforms with RED directive | No |
| Conforms with ATEX-directive | No |
| Conforms with CCC-Ex | No |
| Conforms with CCC | No |
| Conforms with UL | No |
| Conforms with FCC | No |
| Conforms with IC | No |
| EAC certificate available | No |
| Conforms with UKCA (Importer) | Yes (WERMA (UK) Ltd.) |
| Conforms with CMIM | No |



For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.

LineLIGHT Fusion 300 24V RGB Clip

| | |
|-----------------------|----------|
| Conforms with AS-I | No |
| Conforms with DNV | No |
| Conforms with RoHS CN | 25 years |
| Conforms with VdS | No |



For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.